




Alloy Lifting Chain Grade 80

Grade 80 alloy chain is used for overhead lifting.




Code	Diameter in.	Working Load Limit lbs.	Weight / 100 ft lbs.	Dimensions in.			
				A	B Min	C Max	D
CH80SC-732	7/32	2,100	47.0	.680	.319	.787	.217
CH80SC-932	9/32	3,500	73.8	.826	.375	.992	.276
CH80SC-516	5/16	4,500	93.9	.945	.430	1.134	.315
CH80SC-038	3/8	7,100	147.5	1.181	.531	1.417	.394
CH80SC-012	1/2	12,000	254.8	1.535	.689	1.843	.512
CH80SC-058	5/8	18,100	383.0	1.890	.846	2.268	.630
CH80SC-034	3/4	28,300	578.0	2.440	1.008	2.776	.787
CH80SC-078	7/8	34,200	732.4	2.598	1.161	3.118	.866
CH80SC-001	1	47,700	1,021.4	3.071	1.378	3.685	1.024
CH80SC-114	1 1/4	72,300	1,545.5	3.780	1.701	4.528	1.260

Safety Factor 4:1

Grade 100 Chains, Slings and Components also available.


Hammerlock Type Connecting Links (alloy Gr 80)



Code	For chain diameter in.	Working Load Limit lbs.	Weight / ea. lbs.	Dimensions in.	
				A	B
A337-932	9/32	3,500	0.23	1.87	0.60
A337-038	3/8	7,100	0.65	2.69	0.81
A337-012	1/2	12,000	1.50	3.44	1.09
A337-058	5/8	18,100	2.60	4.17	1.35
A337-034	3/4	28,300	3.80	5.06	1.50
A337-078	7/8	34,200	6.30	5.82	2.12
A337-001	1	47,700	9.30	6.48	2.55
A337-114	1 1/4	72,300	17.3	8.48	3.52

Safety Factor 4:1

Eye Cradle Grab Hooks (alloy Gr 80)



Code	For Chain Size in.	Working Load Limit lbs.	Weight / ea. lbs.	Dimensions in.			
				C	E	F	G
EGH80-732	7/32	2,100	.35	1.75	2.69	1.63	.63
EGH80-932	9/32	3,500	.40	1.81	3.44	2.36	.63
EGH80-038	3/8	7,100	1.06	2.63	4.67	3.11	.78
EGH80-012	1/2	12,000	2.26	3.34	5.86	3.94	1.03
EGH80-058	5/8	18,100	4.36	4.08	7.13	4.78	1.25
EGH80-034	3/4	28,300	8.82	5.23	8.99	6.25	1.44
EGH80-078	7/8	34,200	10.40	5.69	9.63	6.50	1.75
EGH80-001	1	47,700	20.90	7.00	12.44	8.09	1.88
EGH80-114	1 1/4	72,300	40.00	8.50	15.56	10.50	2.25

Safety Factor 4:1