




## Grade 40 High Tensile Chain - carbon steel

Grade 40 high tensile chain has a higher resistance to wear than Grade 30. It is a perfect product for farming, heavy duty trucking and similar tasks.



Specifications				
Diameter in.	Inside Dimensions in.		Working Load Limit lbs.	Weight / 100 ft. lbs
	A	B		
1/4	0.90	.44	2600	71
5/16	1.12	.48	3900	102
3/8	1.35	.57	5400	140
1/2	1.70	.75	9200	234

### Safety Factor 3:1

Test certificate available – Do not use for overhead lifting




Self colored		
Drum		
Code	Diameter in.	Pack pi. / ft.
53030	1/4	400
53031	5/16	275
53032	3/8	200
53033	1/2	100



Hot Dipped Galvanized		
Drum		
Code	Diameter in.	Pack ft.
53034	1/4	450
53035	5/16	275
53036	3/8	200
53037	3/8	400

## Stainless Steel Chain 316 L



Code	Diameter		Working Load Limit lbs.	Inside Dimensions in.		Weight per 100 ft lbs.
	mm	in.		A	B	
CHS-564	2	5/64	70	0.14	0.48	5
CHS-018	4	1/8	400	0.27	0.91	20
CHS-316	5,5	3/16	800	0.40	0.96	40
CHS-014	7	1/4	1,300	0.43	1.18	66
CHS-516	8	5/16	1,700	0.50	1.26	86
CHS-038	10	3/8	2,650	0.60	1.31	142
CHS-012	13	1/2	4500	0.72	1.79	242

Safety Factor 4:1

Stainless Steel