



Câble recouvert

Diamètre nominal du câble po.	Diamètre fini du recouvrement po.	Poids approx. par 100 pi. lbs.
1/32	3/64	0.25
3/64	1/16	0.60
1/16	3/32	0.95
1/16	1/8	1.00
3/32	1/8	2.20
3/32	5/32	2.60
3/32	3/16	2.90
1/8	5/32	4.05
1/8	3/16	4.65
1/8	1/4	5.05
5/32	3/16	5.40
5/32	7/32	5.50
3/16	7/32	6.80
3/16	1/4	7.90
3/16	5/16	10.25
1/4	5/16	12.50
5/16	3/8	19.75
5/16	7/16	21.95
3/8	7/16	28.20
3/8	1/2	30.50
3/8	9/16	33.20
7/16	1/2	37.50
7/16	9/16	40.20
1/2	9/16	48.75
1/2	5/8	52.00
1/2	11/16	55.10
5/8	11/16	75.40
5/8	3/4	79.10
5/8	7/8	87.30
3/4	7/8	112.20
3/4	1	122.00
1	1 1/8	197.50
1	1 1/4	217.00
1 1/8	1 1/4	266.00
1 1/4	1 3/8	316.00
1 1/4	1 1/2	356.00

- Nylon 6 (standard)
- Nylon 11 (haute performance)
- Vinyle, uréthane
- Polypropylène
- Polyester (Hytrel)



- Câble miniature disponible sur demande (plus petit que 1/32")
- Câble galvanisé, acier inoxydable 304 et 316 disponibles.



Nous avons développé nos propres recettes et procédés afin d'offrir des couleurs de qualité supérieure.