




Chaîne de levage en acier allié Grade 80

ALLOY LIFTING CHAIN GRADE 80



La chaîne en acier allié Grade 80 est recommandée pour le levage.


Code	Diamètre po.	Charge maximale lbs.	Poids / 100 pi. lbs.	Dimensions po.			
				A	B Min	C Max	D
CH80SC-732	7/32	2,100	47.0	.680	.319	.787	.217
CH80SC-932	9/32	3,500	73.8	.826	.375	.992	.276
CH80SC-516	5/16	4,500	93.9	.945	.430	1.134	.315
CH80SC-038	3/8	7,100	147.5	1.181	.531	1.417	.394
CH80SC-012	1/2	12,000	254.8	1.535	.689	1.843	.512
CH80SC-058	5/8	18,100	383.0	1.890	.846	2.268	.630
CH80SC-034	3/4	28,300	578.0	2.440	1.008	2.776	.787
CH80SC-078	7/8	34,200	732.4	2.598	1.161	3.118	.866
CH80SC-001	1	47,700	1,021.4	3.071	1.378	3.685	1.024
CH80SC-114	1 1/4	72,300	1,545.5	3.780	1.701	4.528	1.260

Facteur de sécurité 4:1

Chaînes, élingues et accessoires Grade 100 aussi disponibles.

Maillons de jonction type Hammerlock (acier allié Gr 80)

HAMMERLOCK TYPE CONNECTING LINKS (ALLOY GR 80)




Code	Pour chaîne diamètre po.	Charge maximale lbs.	Poids / ch. lbs.	Dimensions po.	
				A	B
A337-932	9/32	3,500	0.23	1.87	0.60
A337-038	3/8	7,100	0.65	2.69	0.81
A337-012	1/2	12,000	1.50	3.44	1.09
A337-058	5/8	18,100	2.60	4.17	1.35
A337-034	3/4	28,300	3.80	5.06	1.50
A337-078	7/8	34,200	6.30	5.82	2.12
A337-001	1	47,700	9.30	6.48	2.55
A337-114	1 1/4	72,300	17.3	8.48	3.52

Facteur de sécurité 4:1

Crochets de raccourcissement à oeil (acier allié Gr 80)

EYE CRADLE GRAB HOOKS (ALLOY GR 80)



Code	Pour chaîne diamètre po.	Charge maximale lbs.	Poids / ch. lbs.	Dimensions po.			
				C	E	F	G
EGH80-732	7/32	2,100	.35	1.75	2.69	1.63	.63
EGH80-932	9/32	3,500	.40	1.81	3.44	2.36	.63
EGH80-038	3/8	7,100	1.06	2.63	4.67	3.11	.78
EGH80-012	1/2	12,000	2.26	3.34	5.86	3.94	1.03
EGH80-058	5/8	18,100	4.36	4.08	7.13	4.78	1.25
EGH80-034	3/4	28,300	8.82	5.23	8.99	6.25	1.44
EGH80-078	7/8	34,200	10.40	5.69	9.63	6.50	1.75
EGH80-001	1	47,700	20.90	7.00	12.44	8.09	1.88
EGH80-114	1 1/4	72,300	40.00	8.50	15.56	10.50	2.25

Facteur de sécurité 4:1